



STP CARPET

DECORATIVE MATERIAL



Adjectives:

- SIZE: 1X10 M
- THICKNESS: 1,5 MM

Material:

- NON-WOVEN FABRIC
- ADHESIVE MOUNTING LAYER
- ANTI-ADHESIVE FILM

Colours:

- BRIGHT GREY
- GREY
- BLACK

Application:

- VEHICLE CABIN
- INTERIOR
- TRUNK

SOUND TRANSPARENT MATERIAL IS IDEAL FOR ACOUSTICS INSTALLATION



STP CARPET

DECORATIVE MATERIAL



STP CARPET is decorative lining self-adhesive material, used for automobile cabins, interiors, and trunks lining.
The material is a textile product (non-woven fabric), with an adhesive mounting layer, protected with anti-adhesive film.

Coefficient nomination	Specification	Testing method
Material-to-mounting surface bond strength when peeling off at the angle 90 degrees with dynamic loading, N/cm, min	3	clause 4.4 TS 8729-010-48214265-2002
Anti-adhesive film-to-adhesive layer bond strength, N/cm	0,01-0,20	GOST 17317-88
Adhesive layer resistance to temperature of 60°C during 1 h	The material mustn't peel off the mounting layer	clause 4.4, clause 4.6 TS 8729-010-48214265-2002

Transportation and storage:

The material must be handled under the conditions eliminating moisture penetration.
It's prohibited to drop or bend material packages while handling.
Packages must be transported horizontally, on a plane surface, in any roofed types of transport in compliance with haulage rules for this type of transport under the conditions eliminating mechanical damages, material deformation, and moisture penetration.
Packages must be transported in piles not higher than 3 m. It is prohibited to put any heavy metal and alike objects on packages.
The material must be stored horizontally, on a plane surface, not closer than 1m to heating facilities, under the conditions eliminating moisture and oil penetration and exposure to sunlight.

Exploitation and installation requirements:

The material can be installed on clean dry painted metal, painted, plastic, and other surfaces, including complex surfaces.
To clean the material of dirt, it is recommended to use water with neutral abstergents, not containing organic solvents and alkali.
Upon dismantling, the material can't be reused.
Preparation for installation
In case the material is stored or transported at temperature lower than 0°C, before installation it must be kept at temperature (20±5)°C for not less than 24 h. The working space temperature must be (18-30) °C.
The mounting surface must be cleaned of dust and dirt, unoled with technical solvents and kept until completely dry.
Installation
Anti-adhesive paper must be peeled off step-by-step, smoothly; the detail must be pressed to the surface, avoiding air blisters formation. The material mustn't be installed on dirty, corroded metal surfaces.



<http://www.standartplast.com>